

TECHNICAL DATA SHEET

ARTICLE CODE: SFH 122

FULL BODY HARNESS

*Ideal for use with guided type fall arrester.
Suitable for construction, tower or ladder job.*

Attachment point:

*One common dorsal d-ring for fall arrest.
Two Front D-ring at chest point.*

Construction:

*Dope dyed high quality polyester webbing.
Webbing Width : 44 +/-1 mm
Webbing color: Yellow and Black
Webbing Breaking Strength : 23 kN
Safe Working Load Capacity : 100 kg
Fall indicator to stop reuse of harness after a major fall.
Dual color scheme for easy differentiation.
Stitching Thread Material : High tenacity polyester.
Thread Color : White
Metal Components : Alloy steel, zinc plated, free from sharp edges.*

Adaptability:

*Adjustable thigh strap.
Adjustable chest strap.*

Ergonomics:

Ideally positioned sit strap for extended comfort.

Weight:

1.1 KG (approx.)



Compliance:

*IS: 3521 (Part I) 2021
Conforms to EN 361.*

Application	<ul style="list-style-type: none"> ○ Working at height ○ Fall arrest ○ Ladder climbing
Care instruction and storage	<i>Store in a cool dry place. Avoid damp areas, chemicals, and sharp objects. Keep away from heat.</i>
Cleaning	<i>Use either mild soap and water or a mild, bleach-free cleaning solution that won't damage the webbing.</i>
Inspection	<i>Full-body harnesses should be inspected frequently, both before each use and in every 6 months interval. Damaged or defective harnesses should be discarded from service immediately after inspection.</i>