

## TECHNICAL DATA SHEET

**ARTICLE CODE: SFH 133**

### **FULL BODY HARNESS**



*Ideal for use with guided type fall arrester.  
Suitable for construction, tower or ladder job.*

**Attachment point:**

*One common dorsal d-ring for fall arrest.  
Two Front D-ring at chest point.*

**Construction:**

*Dope dyed high quality polyester webbing.  
Webbing Width : 44 +/-1 mm  
Webbing color: Yellow and Black  
Webbing Breaking Strength : 23 kN  
Safe Working Load Capacity : 100 kg  
Fall indicator to stop reuse of harness after a major fall.  
Dual color scheme for easy differentiation.  
Stitching Thread Material : High tenacity polyester.  
Thread Color : White  
Metal Components : Alloy steel, zinc plated, free from sharp edges.*

**Adaptability:**

*Adjustable thigh & shoulder strap.  
Adjustable chest strap.*

**Ergonomics:**

*Ideally positioned sit strap for extended comfort.*

**Weight:**

*1.2 KG (approx.)*



**Compliance:**  
*IS: 3521 (Part I) 2021  
Conforms to EN 361.*

Application	<ul style="list-style-type: none"> <li>○ Working at height</li> <li>○ Fall arrest</li> <li>○ Ladder climbing</li> </ul>
Care instruction and storage	<i>Store in a cool dry place. Avoid damp areas, chemicals, and sharp objects. Keep away from heat.</i>
Cleaning	<i>Use either mild soap and water or a mild, bleach-free cleaning solution that won't damage the webbing.</i>
Inspection	<i>Full-body harnesses should be inspected frequently, both before each use and in every 6 months interval. Damaged or defective harnesses should be discarded from service immediately after inspection.</i>